PRO LIGNO

www.proligno.ro

Research Article:

EFECTELE TRATAMENTULUI TERMIC DE SCURTĂ DURATĂ ASUPRA UNOR PROPRIETĂȚI ALE LEMNULUI DE TEI

EFFECTS OF SHORT TIME THERMAL TREATMENT ON SOME PROPERTIES OF LIME WOOD

Ioannis BARBOUTIS

Associate Professor – Aristotle University, Faculty of Forestry and Natural Environment Laboratory of Wood Products and Furniture Technology Adresa/Address: 541 24, Thessaloniki, Greece E-mail: jbarb@for.auth.gr

Vasileios VASILEIOU

Professor – Aristotle University, Faculty of Forestry and Natural Environment Laboratory of Wood Products and Furniture Technology Adresa/Address: 541 24, Thessaloniki, Greece E-mail: <u>vass@for.auth.gr</u>

Adromachi MITANI

PhD Student– Aristotle University, Faculty of Forestry and Natural Environment Laboratory of Wood Products and Furniture Technology Adresa/Address: 541 24, Thessaloniki, Greece E-mail: <u>amitani@hotmail.com</u>

Vasiliki KAMPERIDOU

PhD Student – Aristotle University, Faculty of Forestry and Natural Environment Laboratory of Wood Products and Furniture Technology Adresa/Address: 541 24, Thessaloniki, Greece E-mail: <u>vkamperi@for.auth.gr</u>

BIBLIOGRAFIE / REFERENCES

ABRAHAM, J., NEMETH, R., MOLNAR, S. (2010). Thermo-mechanical densification of Pannónia Poplar. 'The Future of Quality Control for Wood & Wood Products', 4-7th May 2010, Edinburgh.

AKYILDIZ, M.H., ATES, S., ÖZDEMIR, H. (2009). Technological and chemical properties of heat-treated Anatolian black pine wood. *African Journal of Biotechnology* Vol. 8 (11), pp. 2565-2572, 3 June, 2009.

ARNOLD M. (2007). Transverse Anisotropy in Thermally Modified Beech and Spruce. 3rd European Conference on Wood Modification. October 15-16th 2007. Bangor (UK).

ATES, S., AKYILDIZ, M.H., ÖZDEMIR, H., GÜMÜSKAYA, E. (2010). Technological and chemical properties of chestnut (Castanea sativa Mill.) wood after heat treatment. *Romanian Biotechnological Letters*. Vol. 15, No.1, 2010.

BÄCHLE, H., ZIMMER, B., WINDEISEN, E., WEGENER, G. (2010). Evaluation of thermally modified beech and spruce wood and their properties by FT-NIR spectroscopy. *Springer, Wood Sci Technol.* Num. 44:421–433.

ESTEVES, B., VELEZ MARQUES, A., DOMINGOS, I., PEREIRA, H. (2007). Influence of steam heating on the properties of pine (*Pinus pinaster*) and eucalypt (*Eucalyptus globulus*) wood. *Springer. Wood Sci Technol.* Vol. 41, Num. 3:193–207.

ESTEVES, M.B., DOMINGOS, J.I., PEREIRA, H.M. (2008). Pine wood modification by heat treatment in air. *Bio resources*. 3(1), 142-154.

HAKKOU, M., PETRISSANS, M., GERARDIN, P., ZOULALIAN, A. (2006). Investigations of the reasons for fungal durability of heat-treated beech wood. *Elsevier, Polymer Degradation and Stability*. Vol. 91, Is. 2, February, pp. 393-397.

KOCAEFE, D., PONCSAK, S., BOLUK, Y. (2008). Effect of Thermal Treatment on the chemical composition and mechanical properties of Birch and Aspen. *Bio Resources*. 3(2), pp. 517-537.

KOCAEFE, D., PONCSAK, S., TANG, J., BOUAZARA, M. (2010). Effect of heat treatment on the mechanical properties of North American jack pine: thermogravimetric study. *Journal of Materials Science*. Vol. 45, Num. 3, 681-687.

MBURU, F., DUMARC'EAY, S., HUBER, F., PETRISSANS, M., GERARDIN, P. (2007). Evaluation of thermally modified Grevillea robusta heartwood as an alternative to shortage of wood resource in Kenya: Characterisation of physicochemical properties and improvement of bio-resistance. *Bioresource Technology*. Num. 98 pp. 3478–3486.

NIEMZ, P., HOFMANN, T., RÉTFALVI, T. (2010). Investigation of chemical changes in the structure of thermally modified wood. *Maderas Ciencia Y Tecnologia*. 12(2):69-78.

OHNESORGE, D., KROWAS, I., BECKER, G. (2008). Results of Durability Tests of Thermal Treated Lumber. *Proceedings of the 51st International Convention of Society of Wood Science and Technology*. November, pp. 10-12.

OLEK, W., BONARSKI, J.T. (2008). Texture changes in Thermally Modified Wood. *Archives of Metallurgy* and *Materials*. Vol 53. pp. 207- 211.

SHI, J.L., KOCAEFE, D; ZHANG, J. (2007). Mechanical behaviour of Quebec wood species heat-treated using ThermoWood process. *Springer, Holz Roh Werkst.* 65:255–259.

TUONG, V.M., LI, J. (2010). Effect of Heat treatment on the change in color and dimensional stability of Acacia hybrid wood. *BioResourses*. 5(2):1257-1267.

WIKBERG, H., MAUNU, S.L. (2004). Characterisation of thermally modified hard - and softwoods by 13^oC CPMAS NMR. *Elsevier, Carbohydrate Polymers.* Vol. 58, Is. 4, 7 December, pp. 461-466.

YAO, C., YONGMING, F., JIANMIN, G., HOUKUN, L. (2010). Coloring characteristics of in situ lignin during heat treatment. *Springer, Wood Science and Technology*. DOI: 10.1007/s00226-010-0388-5.

YILDIZ, S., GEZERB, E.D., YILDIZ, U. C. (2006). Mechanical and chemical behavior of spruce wood modified by heat. *Building and Environment*. Vol. 41, Is. 12, pp. 1762-1766.

- *** DIN 52185:1976. Testing of wood; compression test parallel to grain.
- *** ISO 3130:1975. Wood Determination of moisture content for physical and mechanical tests.
- *** ISO 3131:1975. Wood Determination of density for physical and mechanical tests.

*** ISO 3133:1975. Wood - Determination of ultimate strength in static bending.

*** ISO 3348:1975. Wood - Determination of impact bending strength.

- *** ISO 3350:1975. Wood Determination of static hardness.
- *** ISO 4859:1982. Wood Determination of radial and tangential swelling.