

**Research Article:**

**O INTROSPECTIVĂ A DEGRADĂRII  
LEMNULUI DE FAG (*Fagus sylvatica* L.)  
EXPUS TIMP ÎNDELUNGAT ÎN  
EXTERIOR, DEASUPRA SOLULUI**  
Partea 1: Tipuri de degradare și influența  
tratamentelor de suprafață, relevate prin  
evaluare nedistructivă după 7 ani de  
expunere

**AN INSIGHT INTO BEECH WOOD (*Fagus  
sylvatica* L.) DEGRADATION IN  
OUTDOORS, ABOVE GROUND, LONG-  
TIME EXPOSURE**  
Part 1: Degradation and influence of  
surface treatments revealed by non-  
destructive evaluation after 7 years

**Maria Cristina TIMAR\***

Prof.dr.eng. – TRANSILVANIA University in Brasov – Faculty of Wood Engineering  
Adresa/Address: B-dul Eroilor nr. 29, 50036 Brasov, Romania  
E-mail: [timar@unitbv.ro](mailto:timar@unitbv.ro)

**Emanuela BELDEAN**

Lect.dr.eng. – TRANSILVANIA University in Brasov – Faculty of Wood Engineering  
Adresa/Address: B-dul Eroilor nr. 29, 50036 Brasov, Romania  
E-mail: [ebeldean@unitbv.ro](mailto:ebeldean@unitbv.ro)

**Octavia ZELENIU**

Lect.dr.eng. – TRANSILVANIA University in Brasov – Faculty of Wood Engineering  
Adresa/Address: B-dul Eroilor nr. 29, 50036 Brasov, Romania  
E-mail: [zoctavia@unitbv.ro](mailto:zoctavia@unitbv.ro)

**Anca VARODI**

Researcher dr. eng.- TRANSILVANIA University in Brasov, ProDD Institute  
Adresa/Address: Str. Institutului nr.10, Brasov, Romania  
E-mail: [anca.varodi@unitbv.ro](mailto:anca.varodi@unitbv.ro)

**BIBLIOGRAFIE / REFERENCES**

- BELDEAN, E. (2009). Dimensional Stabilisation of Wood - A Practical Issue of Topical Interest. În PRO LIGNO, vol 5(4):45-52.
- BOXALL, J., CAREY, J.K., MILLER, E.R. (1992). The effectiveness of end-grain sealers in improving paint performance on softwood joinery. Part 3: Influence of coating type and wood species on moisture content and fungal colonisation. Holz als Roh und Werkstoff, 50:227-232.
- BRISCHKE, C., RAPP, A.O. (2008). Influence of wood moisture content and wood temperature on fungal decay in the field: observations in different micro-climates. Wood Science and Technology, 42(8):663-677, DOI: 10.1007/s00226-008-0190-9.
- CAREY, J.K., BRAVERY, A.F. (1986). Co-operative research project on L-joint testing: Progress report to March 1986. IRG/WP/2272. Inter. Res. Group on Wood Preservation, Stockholm, Sweden. p.16.
- CLAUSEN, C.A., LINDNER, D.L. (2011). Shading Aboveground L-joint and Lap-joint Tests: Comparison of White Pine and Sugar Maple Test Assemblies. Forest Products Journal, 61(3):265-269.
- COOKSON, L.J. (2010). Preservative treatments suitable for hardwood window joinery. International Biodeterioration & Biodegradation, 64(7):652-658.
- COOPER, P.A., Alexander, D.L. (1993). What is chemical fixation? Chromium-Containing Waterborne Wood Preservatives: Fixation and Environmental Issues. Forest Products Society (Madison, WI): 7-13.
- DE SOUZA, A., GAYLARDE, C. (2002). Bio deterioration of varnished wood with and without biocide: implications for standard test methods. In International Bio deterioration & Biodegradation, 49(1):21-25.
- DE VETTER, L., VAN ACKER, J. (2010). Accelerated L-joint performance testing of organosilicon treated wood. IRG 10 30551. The International Research Group on Wood Preservation - The 41<sup>th</sup> IRG Annual Meeting, Biarritz-France.
- DESPOT, R. (1998). Mechanism of infection of fir wood joinery; Part 2: Sequence and intensity of attack of micro organism, Drvna Industrija (Wood Industry), 49(3):135-144.

\* Autor corespondent / Corresponding author

EATON, R.A, HALE, M.D.C. (1993). Wood decay, pests and protection. Chapman & Hall, London.

HIGHLEY, T.L. (1993). Above-ground performance of surface-treated hardwoods and softwoods. *Wood Protection* 2(2):61-66.

HON, D.N.S. (2001). Weathering and photochemistry of wood. In: Hon D.N.S., Shiraishi, N. (eds): *Wood and cellulose chemistry*. Dekker, New York, p. 513–546.

LEBOW, S., CLAUSEN, C. (2010). Challenges in accelerated testing of durable wood products. *Wood and Fiber Product Seminar*. VTT and USDA joint activity. VTT Symposium 263 Helsinki, Finland: VTT, c2010. p. 128-136. ISBN 978-951-38-7589-3.

MALDAS, D.C., KAMDEN, D.P. (1998a). Surface Tension and Wettability of CCA-Treated Red Maple, *Wood and Fiber Science*, 30(4):368-373.

MALDAS, D.C., KAMDEN, D.P. (1998b). Surface characterization of chromated copper arsenate (CCA)-treated red maple, *Journal of Adhesion Science and Technology*, 12(7):763-772.

MILITZ, H., HILL, C. (Eds). (2005). *Wood modification: Processes, Properties and Commercialisation*. Proc. 2<sup>nd</sup> European Conference on Wood Modification, Goettingen, ISBN 3-00-017207-6.

MOLNAR, S., NEMETH, R., FEHER, S. et al. (2001). Technical and technological properties of hungarian beech wood consider the red heart, *Drevarsky Vyskum*, 46(1): 21-29.

PFEFFER, A., HOEGGER, P.J., KU, U., MILITZ, H. (2012b). Fungal colonisation of outside weathered modified wood, *Wood Science and Technology*, 46:63–72.

PFEFFER, A., MAI, C., MILITZ, H. (2012a). Weathering characteristics of wood treated with water glass, siloxane or DMDHEU. *Eur. J. Wood Prod.* 70:165–176.

RABERG, U., EDLUND, M.L., NASKO, T., LAND, C.J. (2005). Testing and evaluation of natural durability of wood in above ground conditions in Europe - an overview, *J. Wood Science*, 51:429-440.

SCHAUWECKER, C., ZAHORA, A., PRESTON, AL. (2010). Relative Performance of treated and untreated L-joints under UC3A and UC3B Conditions Using Two Exposure Conditions. IRG/WP 10-60297. The International Research Group on Wood Preservation - The 41st IRG Annual Meeting, Biarritz, France.

TIMAR, M.C., BELDEAN, E. (2006). Aspects of wood degradation revealed by a modified L-joint test, In: *Bulletin of Transilvania University of Brasov*, vol 13(48):335-342.

TIMAR, M.C., BELDEAN, E. (2007a). Aspects of wood degradation and effects of surface impregnation of beech and fir wood with reactive resins revealed by a modified L-joint test, In: *Proceedings of the Third European Conference on Wood Modification*, Cardiff, UK, p. 221-224, ISBN 184-220-096-8.

TIMAR, M.C., BELDEAN, E. (2007b). Outcomes of a Long-Term Modified L-joint Test – Parts 1-3. In: *Proceedings of International Conference ICWSE*, Brasov, p. 171-190.

TIMAR, M.C., BELDEAN, E., MIHAI, D. (2005). Opportunities and limits of wood improvement by surface treatment with reactive resins. *Proceedings of the Second European Conference on Wood Modification*, Goettingen, p. 178-185, ISBN 3-00-017207-6.

TIMAR, M.C., BELDEAN, E., ZELENIUIC, O., LICA, D. (2008). Outcomes of a modified L-joint test in Romania – opportunities for a complex evaluation of the performance of wood in outdoor above ground conditions. In: *Socio-economic perspectives of treated wood for the common European market*, *Proceedings of COST E37 Final Conference*, Bordeaux, p. 107-117.

VAN ACKER, J., PEEK, R.D. (Eds). (2008). *Socio-economic perspectives of treated wood for the common European market*. *Proceedings of COST E37 Final Conference*, Bordeaux.

VAN ACKER, J., STEVENS, M. (1997). A new concept for the evaluation of wood durability for out of ground contact using accelerated L-joint testing, IRG/WP 97-20123, Stockholm, Sweden.

VAN ACKER, J., STEVENS, M. (2003). Biological durability of wood in relation to end-use--Part 2: The use of an accelerated outdoor L-joint performance test. *European Journal of Wood and Wood Products*, 61(2):125-132.

\*\*\*SR EN 335:2007. Durability of wood and wood- based products - Definition of use classes - Part 1: General.

\*\*\*SR EN 330:1997. Wood preservatives. Field test method for determining the relative protective effectiveness of a wood preservative for use under a coating and exposed out-of-ground contact. L-joint method.

\*\*\*CEN/TS 12037:2003. Wood preservatives. Field test method for determining the relative protective effectiveness of wood preservative exposed out of ground contact: Horizontal lap-joint method.

\*\*\*SR EN 252:1995. Field test method for determining the relative protective effectiveness of a product for wood preservative in ground contact.

[http://www.wolman.de/en/infocenter\\_wood/from\\_tree\\_to\\_wood/wood\\_species/beech/index.php](http://www.wolman.de/en/infocenter_wood/from_tree_to_wood/wood_species/beech/index.php)

[http://www.erlauusa.com/Outdoor\\_Furniture.html](http://www.erlauusa.com/Outdoor_Furniture.html)

<http://www.wood-database.com/lumber-identification/hardwoods/european-beech/>

<http://www.timberwood.ro/products.html>,

<http://dfwm.ugent.be/woodlab/docs/gottingen/cristescu.pdf>,

<http://www.alibaba.com/countrysearch/RO/beech-wood.html>

[www.Policolor.ro](http://www.Policolor.ro)