ONLINE ISSN 2069-7430
ISSN-L 1841-4737

PRO LIGNO
www.proligno.ro

Vol. 8 N° 4 2012
pp. 18-26

Research Article:

CARACTERISTICILE DE ÎNCĂLZIRE ALE RĂŞINOASELOR ÎN CÂMP ELECTRIC DE ÎNALTĂ FRECVENȚĂ

HEATING CHARACTERISTICS OF SOFTWOODS IN A HIGH FREQUENCY FIELD

Ciprian LĂZĂRESCU
Research Associate - The University of British Columbia – Faculty of Forestry, Department of Wood Science
Adresa/Address: 2424 Main Mall, Vancouver, BC, V6T 1Z4, Canada.
E-mail: ciprilaz@mail.ubc.ca

Bogdan BEDELEAN
Assist.dr.eng. – TRANSILVANIA University in Brasov – Faculty of Wood Engineering
Adresa/Address: B-dul Eroilor nr. 29, 50036 Brasov, Romania
E-mail: bedelean@unitbv.ro

Stavros AVRAMIDIS*
Prof. - The University of British Columbia – Faculty of Forestry, Department of Wood Science
Adresa/Address: 2424 Main Mall, Vancouver, BC, V6T 1Z4, Canada.
E-mail: stavros.avramidis@ubc.ca

BIBLIOGRAFIE / REFERENCES

Avramidis S, Liu F, Neilson BJ (1994) Radio-frequency/vacuum drying of softwoods: drying of thick western redcedar with constant electrode voltage. Forest Prod. J. 44(1):41-47.

CFIA (2005) Guidelines for the Phytosanitary Certification of Lumber for Export. Canadian Food Inspection Agency. Online at: http://www.inspection.gc.ca/plants/forestry/exports/lumber-for-export/eng/1319344061800/1319344217966

Elustondo D, Avramidis S, Zwick R (2005) The demonstration of increased lumber value using optimized lumber sorting and radio frequency vacuum drying. Forest Prod. J. 55(1):76-83.

Halbach K, Holsinger R (1976) Superfish - A Computer Program for Evaluation of RF Cavities with Cylindrical Symmetry. Particle Accelerators 7: 213-222.

Jiao, S., Tang, J., Johnson, J.A., Tiwari, G., Wang, S. 2011. Determining radio frequency heating uniformity of mixed beans for disinfestation treatments. Transactions of the ASABE. 54(5):1847-1855

LAACG (2011) Download Area for Poisson Superfish V7.19. Los Alamos Accelerator Code Group. Online at: http://laacg1.lanl.gov/laacg/services/download_sf.phtml

Lazarescu C, Avramidis S (2011) Radio – frequency heating kinetics of softwood logs. Drying Technology 29(6):673-681.

Lazarescu C, Avramidis S (2012) Heating characteristics of western hemlock (*Tsuga Heterophylla*) in a high frequency field. Eur. J. Wood Prod. 70:489–496.

Lazarescu C, Plattner A, Hart F, Breuil C, Avramidis S (2009) Pasteurization of Hemlock by Radio Frequency Heating: a preliminary study. Forest Prod. J. 59(4):79-83.

Milota MR, Danielson JD, Boone RS, Huber DW (1991). Quality drying of softwood lumber: guidebook – checklist. General technical report FPL; IMP-GTR-1. Online at: http://msucares.com/forestproducts/topics/documents/softwood_drying.pdf

MFLNRO (2009) Investing in our forests. Ministry of Forests, Lands and Natural Resource Operations in Canada. Online at: http://www.for.gov.bc.ca/mof/fcbc/FCBC-Opportunities.pdf

Norimoto M, Hayashi S, Yamada T (1971) Anisotropy of dielectric constant in coniferous wood. Holzforschung 51:12–32.
Torgovnikov GI (1993) Dielectric Properties of Wood and Wood-Based Materials. Springer-Verlag, New York.

* Autor corespondent / Author to whom all correspondence should be addressed