

Research Article:

**EFFECTUL RUGOZITĂȚII FURNIRELOR
ASUPRA ÎNCLEIERII ȘI ASUPRA UNOR
PROPRIETĂȚI MECANICE ALE
PLACAJULUI**

**THE EFFECT OF VENEERS
ROUGHNESS ON BONDING AND SOME
MECHANICAL PROPERTIES OF
PLYWOOD**

Ismail AYDIN*

Prof. dr.- Karadeniz Technical University, Faculty of Forestry
Adresa/Address: Forest Industry Engineering Department, 61080 Trabzon, Turkey
E-mail: aydin@ktu.edu.tr

Cenk DEMIRKIR

Lecturer, dr.- Karadeniz Technical University, Faculty of Forestry
Adresa/Address: Forest Industry Engineering Department, 61080 Trabzon, Turkey
E-mail: cenk@ktu.edu.tr

Semra COLAK

Prof. Dr.- Karadeniz Technical University, Faculty of Forestry
Adresa/Address: Forest Industry Engineering Department, 61080 Trabzon, Turkey
E-mail: colak@ktu.edu.tr

Emilia – Adela SALCĂ

Lecturer, dr.eng. – TRANSILVANIA University in Brasov – Faculty of Wood Engineering
Adresa/Address: B-dul Eroilor nr. 29, 50036 Brasov, Romania
E-mail: emilia.salca@unitbv.ro

BIBLIOGRAFIE / REFERENCES

- Aguilera A, Vega M, Meausoone PJ (2007) Effects of grain angle on the amplitudes of acoustic emission and surface roughness in wood machining. *Wood Sci Technol* (41):373–381.
- Aydin I (2004) Activation of wood surfaces for glue bonds by mechanical pre-treatment and its effects on some properties of veneer surfaces and plywood panels. *Applied Surface Science* (233):268–274.
- Aydin I, Colakoglu G (2005) Effects of surface inactivation, high temperature drying and preservative treatment on surface roughness and colour of alder and beech wood. *Applied Surface Science* (252):430–440.
- Aydin I, Demirkir C (2010) Activation of Spruce Wood Surfaces by Plasma Treatment After Long Terms of Natural Surface Inactivation. *Plasma Chemistry and Plasma Processing* (30):697–706.
- Bozkurt AY (1992) *Wood Anatomy*. Faculty of Forestry, Istanbul University, Pub. no. 415, Istanbul, Turkey.
- Chow S, Chunsi KS (1979) Adhesion strength and wood failure relationship in wood-glue bonds. *MokuzaiGakkaishi* 25(2):125–31.
- Davis EM (1962) *Machining and related characteristics of United States hardwoods*. Washington, DC, Technical bull. no. 1267. USDA, pp. 68.
- DIN EN 636 (2012). *Plywood - Specifications; German version*.
- Dunky M, Niemz P (2002) *Holzwerkstoffe und Leime - Technologie und Einflussfaktoren*, Springer Verlag Berlin.
- EN 314-2 (1996). *Plywood; Bonding Quality, Part 2, Requirements*, CEN, Brüssel.
- Follrich J, Vay O, Veigel S, Muller U (2010) Bond strength of end-grain joints and its dependence on surface roughness and adhesive spread. *J Wood Sci* (56):429–434.

* Autor corespondent / Author to whom all correspondence should be addressed

- Gurău L, Mansfield-Williams H (2007) Separation of processing roughness from anatomical irregularities and fuzziness to evaluate the effect of grit size on sanded European oak. *Forest Prod J* 57(1/2):110–115.
- Habenicht G (2002) *Kleben – Grundlagen, Technologien, Anwendungen*. 4. Aufl age. Springer, Berlin.
- Irle M, Barbu MC, Reh R (2013) Chapter 10 "Wood composites", Chapter 1 in "Handbook for Wood Chemistry and Wood Composites" by Roger Rowell. The 2nd Edition. CRC Press Taylor and Francis Group.
- Kilik M, Hiziroglu S, Burdulu E (2006) Effect of machining on surface roughness of wood. *Building and Environment* (41):1074–1078.
- Marra AA (1992) *Technology of wood bonding – principles in practice*. Van Nostrand Reinhold, New York, pp. 231–232.
- Mitchell P, Lemaster R (2002) Investigation of machine parameters on the surface quality in routing soft maple. *Forest Products Journal* 52(6):85–90.
- Namara US, Waters O (1970) Comparison of the rate of glueline strength development for oak and maple. *Forest Product Journal* 20(3):34–5.
- Neese JL, Reeb JE, Funck JW (2004) Relating traditional surface roughness measures to glue-bond quality in plywood. *Forest Prod. J.* 54(1):67–73.
- Ors Y, Colakoglu G, Aydin I, Colak S (2002) Comparison of Some Technical Properties of Plywood Produced From Beech, Okoume and Poplar Rotary Cut Veneers in Different Combinations. *Journal of Polytechnic* 5(3):257-265.
- Sensogut C, Ozalp G, Yesil H (2009) The effect of borax pentahydrate addition to urea formaldehyde on the mechanical characteristics and free formaldehyde content of plywood. *International Journal of Adhesion & Adhesives* (29):589–592.
- Shupe TF, Hse CY, Wang WH (2001) An investigation of selected factors that influence hardwood wettability. *Holzforschung* (55):541–548.
- Tan PL, Sharif S, Sudin I (2012) Roughness Models for sanded wood surfaces. *Wood Sci. Technol.* (46):129-142.
- Vick CB (1999) *Adhesive bonding of wood materials*. In: *Wood handbook – wood as an engineering material*. US Department of Agriculture, Forest Products Laboratory, Madison, WI.
- Wengert EM, Lamb FM (1994) *A handbook for improving quality and efficiency in rough mill operations*. Princeton, WV: R.C. Byrd Hardwood Technology Center pp. 107.